

# MANUAL EXTENDER

**RAISE THE STREAM  
CLEAR OBSTRUCTIONS  
PROTECT THE RIG**

## 12" or 18" (305 mm or 457 mm) rise options

- Raises stream to prevent damage to apparatus equipment
- More ergonomic operating position

## Monitor operates in raised or lowered position

- Full 360° rotation in either position

## Automatically locks in up/down position

- Cannot be accidentally unlocked
- Prevents unintended extension under pressure
- Prevents unintended collapse when extended

## Built-in sensor for connection to cab indicator light

- Notifies personnel when Extender is NOT stowed and locked

## 3" waterway

- Capable of 1250 gpm (4750 LPM) flow



Easy-op latch design for safe and simple deployment



## Options:

### MOUNTING OPTIONS

- Dual bracket
- Plate and saddle bracket

### INLET OPTIONS

- 3" Victaulic
- 3" NPT
- 3" NPT with 150# Flange\*

### OUTLET OPTIONS

- 3" NPT
- 3" NPT with 150# Flange\*

\*Flange P/N 31030011 sold separately

**ELKHART BRASS**



SAFE  FLEET  
Driving Safety Forward™

# MANUAL EXTENDER™

## ORDERING GUIDE

**1**

Select one of the Extender packages below

<b>08599201 – 12" (3045 mm)</b>	<b>08599211 – 12" (305 mm)</b>	 <p><b>Dual Saddle Bracket</b></p>
<b>08599001 – 18" (457 mm)</b>	<b>08599011 – 18" (457 mm)</b>	
Manual Extender	Manual Extender	 <p><b>Plate and Saddle Bracket</b></p>
3" MNPT inlet	3" Victaulic inlet	
3" MNPT outlet	3" MNPT outlet	
Dual saddle brackets	Dual saddle brackets	
<b>08599212 – 12" (305 mm)</b>	<b>08599213 – 12" (305 mm)</b>	
<b>08599012 – 18" (457 mm)</b>	<b>08599013 – 18" (457 mm)</b>	
Manual Extender	Manual Extender	
3" MNPT inlet	3" Victaulic inlet	
3" MNPT outlet	3" MNPT outlet	
Plate and saddle bracket	Plate and saddle bracket	

**2**

Select monitor option (sold separately)

**Recommended**

- Stinger® 2.0 (deck mount)
- Stinger® 2.0 (portable)

See Stinger 2.0 selector guide for mounting connection options



**Stinger 2.0**

**3**

Select nozzle option (sold separately)

- SM-1000 2.5" Automatic nozzle
- SM-1250 2.5" Automatic nozzle
- 282A Stream Shaper (no charge when purchased with Stinger 2.0)
- Quad Stacked Tips (no charge when purchased with Stinger 2.0)



**SM Series  
Automatic Nozzle**

This is intended as a guide only. For all options and configurations, please contact your Elkhart Brass Regional Sales Manager or Customer Service.

**ELKHART BRASS**

04-22

Copyright ©2022 Safe Fleet and its subsidiaries. All rights reserved. No part of this publication may be reproduced by any means without written permission from Safe Fleet. The information in this publication is believed to be accurate. However, Safe Fleet does not make any representation or warranty to that effect and does not assume responsibility for any consequences resulting from use of such information. Revisions or new editions of the publication may be issued (or not issued) in our discretion to incorporate such changes.

+1 574-295-8330  
elkhartbrass.com

SAFE FLEET  
Driving Safety Forward™