

Chief XD™



5" Mid-Range Chief XD Nozzle

The Chief XD takes the industry standard for handline nozzles to a whole new level. It offers accurate high volume flows at low tip pressures and is built tough like no other nozzle for Xtreme Duty, or XD. The Chief XD is the only handline nozzle that offers a forged shutoff body and forged metal bale handle for maximum strength. It also includes as standard a full round metal ball for the best stream performance, as well as fixed molded urethane or spinning stainless steel metal teeth that don't break. All indicators and markings are laser etched, with no labels to peel off or scratch. Ergonomic grip inserts help with handling and can also be color coded. It's durability and efficiency ensures an embedded level of safety for you and your crew, fire after fire.

- Accurate & wide range of flows
- Available with 50, 75, or 100 psi operating pressure
- Fixed gallonage from straight stream to full fog
- Forged aluminum shutoff body and bale handle
- Laser etched markings
- Dual drive shutoff with full round metal ball
- Spinning stainless steel or fixed molded urethane teeth
- Color coded bumper along with bale handle & pistol grip inserts



1.5" Mid-Range Chief XD Nozzle

Chief XD Tips

Mid-Range 1.5" / Rigid Base

150 @ 50	125 @ 75	95 @ 100
160 @ 50	150 @ 75	125 @ 100
175 @ 50	175 @ 75	150 @ 100
	185 @ 75	175 @ 100
	200 @ 75	



Mid-Range Tip

High-Range 1.5" / Rigid Base

185 @ 50	250 @ 75	250 @ 100
210 @ 50	300 @ 75	
250 @ 50		
265 @ 50		



High-Range Tip

Chief XD Nozzles

Mid-Range 1.5" / Free Swivel Base

150 @ 50	125 @ 75	95 @ 100
160 @ 50	150 @ 75	125 @ 100
175 @ 50	175 @ 75	150 @ 100
	185 @ 75	175 @ 100
	200 @ 75	



1.5" Mid-Range

High-Range 1.5" / Free Swivel Base

185 @ 50	250 @ 75	250 @ 100
210 @ 50	300 @ 75	
250 @ 50		
265 @ 50		

High-Range 2.5" / Free Swivel Base

185 @ 50	250 @ 75	250 @ 100
210 @ 50	300 @ 75	
250 @ 50		
265 @ 50		



1.5" Mid-Range

Chief XD Nozzles with Pistol Grip

Mid-Range 1.5" / Free Swivel Base

150 @ 50	125 @ 75	95 @ 100
160 @ 50	150 @ 75	125 @ 100
175 @ 50	175 @ 75	150 @ 100
	185 @ 75	175 @ 100
	200 @ 75	



2.5" High-Range

High-Range 1.5" / Free Swivel Base

185 @ 50	250 @ 75	250 @ 100
210 @ 50	300 @ 75	
250 @ 50		
265 @ 50		

High-Range 2.5" / Free Swivel Base

185 @ 50	250 @ 75	250 @ 100
210 @ 50	300 @ 75	
250 @ 50		
265 @ 50		

Specify when ordering:

- Flow rate & pressure
- Bumper, bale handle, and pistol grip insert color (orange standard)
- Spinning stainless steel metal teeth (standard) or fixed molded urethane teeth
- Inlet threads



Nozzle Options

Colors

Choose bumper color, bale insert, and pistol grip insert color (orange is standard on Chief XD)



Orange



Red



Yellow



Green



Blue



Black



Glow

Teeth

Choose from spinning stainless steel metal or fixed molded urethane teeth.



Spinning Stainless Steel
(Standard)



Fixed Molded Urethane

Inlet Threads

- NHT (Standard)
- NPSH
- BSP
- Others available. Please provide thread spec: ODM (Outside Diameter Male), TPI (Threads Per Inch), and Province/City. (Ex. 3.030 x 8 NYFD Thread)

Use our new Online Configurator to design your own XD Nozzle!
XDconfigurator.com

XD™ Shutoffs



2.5" XD Shutoff with 188-XD Smooth Bore

Elkhart Brass XD Shutoffs and Playpipes are designed and constructed for rugged use and reliable performance. They are built strong with forged shutoff bodies and forged metal bale handles earning the title Xtreme Duty, or XD. They provide an excellent foundation for break-apart applications using smooth bore or fog nozzle tips. Elkhart Brass XD Shutoffs are available with a variety of options, including built-in smooth bore discharges that can be used with fog nozzle tips for maximum versatility.

- Dual drive shutoff with full round metal ball
- Forged aluminum shutoff body
- Forged metal bale handle
- Attention to detail in waterway alignment and smoothness of operation throughout
- Laser etched markings
- Color coded pistol grip and bale handle inserts



1.5" XD Shutoff with ST-185-XD Smooth Bore

XD Shutoffs

1.5" Shutoff Free Swivel Base

1.5" Inlet 1.5" Outlet

1.5" Shutoff Free Swivel Base / Pistol Grip

1.5" Inlet 1.5" Outlet

2.5" Shutoff Free Swivel Base

2.5" Inlet 1.5" Outlet

2.5" Shutoff Free Swivel Base / Pistol Grip

2.5" Inlet 1.5" Outlet

XD Shutoffs with Integral Smooth Bore

Available discharge sizes: 7/8", 15/16", 1", 1-1/6", 1-1/8"
1-3/16", 1-1/4"

1.5" Shutoff Free Swivel Base

1.5" Inlet 1.5" Outlet

1.5" Shutoff Free Swivel Base / Pistol Grip

1.5" Inlet 1.5" Outlet

2.5" Shutoff Free Swivel Base

2.5" Inlet 1.5" Outlet

2.5" Shutoff Free Swivel Base / Pistol Grip

2.5" Inlet 1.5" Outlet

XD Playpipes

2.5" Shutoff Free Swivel Base

2.5" Inlet 1.5" Outlet

2.5" Shutoff Free Swivel Base / Ladder Hook

2.5" Inlet 1.5" Outlet



Specify when ordering:

- Bale and Pistol Grip insert colors (black standard)
- Inlet/Outlet threads
- Integral Smooth Bore discharge size (if applicable)



1.5" XD Shutoff



1.5" XD Shutoff w/
Pistol Grip



2.5" XD Shutoff



2.5" XD Shutoff w/
Pistol Grip



1.5" XD Shutoff w/
Smooth Bore



1.5" XD Shutoff w/
Smooth Bore &
Pistol Grip



2.5" XD Shutoff w/
Smooth Bore



2.5" XD Shutoff w/
Smooth Bore &
Pistol Grip



2.5" XD Playpipe



2.5" XD Playpipe w/
Ladder Hook

Elkhart Brass took classic smooth bore tips to the next level. The 185-XD, 187-XD, 188-XD, ST-185-XD, and ST-190-XD smooth bore tips feature durable urethane bumpers and laser etching. Extra knurling has also been added for increased control and grip.

- Lightweight aluminum construction
- Laser etched flow rates
- Durable urethane molded bumper



1.5" XD Shutoff with 187-XD Smooth Bore

Smooth Bore Single Tip

- 185-XD** 1.5" Inlet / 1.5" Outlet / 4.5" Length
Available Discharges: 7/8", 15/16", 1", 1-1/16", 1-1/8", 1-3/16", 1-1/4"
- 187-XD** 1.5" Inlet / 4.5" Length
Available Discharges: 7/8", 15/16", 1", 1-1/16", 1-1/8", 1-3/16", 1-1/4"
- 188-XD** 1.5" Inlet / 7.0" Length
Available Discharges: 7/8", 15/16", 1", 1-1/16", 1-1/8", 1-3/16", 1-1/4"



185-XD 187-XD 188-XD

Smooth Bore Stacked Tips

- ST-185-XD** 1.5" Inlet / 6.625" Length / FDNY Stack
Available Discharges: 1/2" & 7/8", 15/16", 1-1/8", 1-3/16"
- ST-185-XD-IFD** 1.5" Inlet / 7.625" Length / Indy Stack
Available Discharges: 1-1/8" & 1-1/4"
- ST-185-XD-CAFS** 1.5" Inlet / 6.625" Length / CAFS Stack
Available Discharges: 15/16" & 1-1/8"
- ST-190-XD** 1.5" Inlet / 9.0" Length / Triple Stack
Available Discharges: 1" & 1-1/8" & 1-1/4"



ST-185-XD ST-185-XD-IFD ST-185-XD-CAFS ST-190-XD

Specify when ordering:

- Inlet threads (FNH or FNPSH)
- Smooth Bore discharge size (if applicable)