

Single Body Apparatus

Single Body Apparatus Valves come with an integral actuator of your choice - direct or remote. Designed specially for reliability, ease of installation and ease of use. The Single Body ball valve is designed to the industry standard dimensions. Features the option to select one of eight handle positions with removal of a single bolt. It's that simple. Pair Single Body valves with Unibody Apparatus line for a total apparatus valve solution.

- 1" & 1.5" body sizes
- Dual self-adjusting seats provide bi-directional sealing
- Corrosion resistant brass body with stainless steel valve ball
- Eight position handle adjustment in 45° increments

Remote Handle (R1)



Direct Handle (TS)

Size	ACTUATOR				MATERIALS			BALL TYPE	WORKING PRESSURE (psi)	C _v VALUE	ELKHART MODEL	Akron Model
	R1	TS	Travel	Locking	Body	Ball	Seat					
1"	•		90°		Brass Alloy 844	316 Stainless Steel	Hytrel	Round	250	81	SB10/R1	8810/R-1
1½"	•		90°		Brass Alloy 844	316 Stainless Steel	Hytrel	Round	250	206	SB15/R1	8815/R-1
1"		•	105°	•	Brass Alloy 844	316 Stainless Steel	Hytrel	Round	250	81	SB10/TS	8810/TS
1½"		•	105°	•	Brass Alloy 844	316 Stainless Steel	Hytrel	Round	250	206	SB15/TS	8815/TS

NOTE: See 8-15 for Single Body Adapters.